

Fashion Outlets of Chicago
Barricade Graphics Guidelines

Barricade Material and Programs

- A. Where LL has a barricade recycle program in place, Landlord will install barricade at Tenant's expense. Tenant is required to use Landlord vendor for barricade graphics. In the event installation of barricade is otherwise specified by Landlord or Tenant Lease agreement the following barricade specification must be used:
- Face to be a minimum of 1/4" MDF with 6 mil factory applied vinyl surface. Minimum class C certification for flame spread.
 - Wall system is to be constructed of fully welded extruded aluminum frame material.
 - All seams must be flush.
 - In no event will metal studs/drywall be allowed.
- B. Construction barricade graphics installed by vendor other than LL approved vendor will need to meet the following requirements:
- Complete attached Boston Barricade Supplied Graphics materials Release Form (found on page 3 of this manual).
 - Apply graphics to barricade by following specific instruction found on the Boston Barricade Supplied Graphics form (found on page 3 of this manual).

Barricade Graphics Design Guidelines

- i. Full barricade wrap of retailer graphics to cover 100% of barricade surface (found on pages 4-6 of this manual).
- ii. Extreme Sized Barricades which exceed 90 linear feet are given special exceptions. Graphics will be approved on an on project basis. Graphics and painting should be consistent and cover entire barricade. The percentage of graphics will be taken into consideration as per the length and height of the barricade.
- iii. Exterior Barricades should be either a molded product or ply-wood but should adhere to the same standards above.
- iv. Graphics installed by Tenant must be completed within 3 days of construction commencement.
- v. Information should be provided to Landlord by Tenant two weeks before lease execution, if graphics are to be installed by Landlord.



SUPPLIED GRAPHIC MATERIALS RELEASE FORM

By signing this form I _____ certify that I have read this form entirely. I understand and assume full responsibility for supplied graphic materials that could possibly cause damage the surface of the barricade if the correct SAV material with a removable adhesive system is not provided for installation.

Boston Barricade Company's modular barricade systems are comprised of a virtually seamless interlocking aluminum frame with a vinyl coated face. In order to enhance the longevity of our systems and to prevent damage to our barricades surface we require that any graphics being applied to the surface of our barricades be a SAV (Self Adhering Vinyl) material with a removable adhesive system*. We require that all applied graphics have a removable adhesive system to prevent any damage to the vinyl coating.

We have had great success with our proprietary Flexcon formulated removable SAV (BBCAR01) and highly recommend it's use for any graphics being applied to our barricade surface. Please contact us with any questions pertaining to printing, product procurement. Acceptable alternatives listed below**.

NAME

DATE

*SAV is the only method of fastening and/or application of graphics permitted by Boston Barricade on our modular system Permanent Adhesives, Screws, Drilling, Fixed Structures or any other method of fastening graphics to our barricade system is not permitted by Boston Barricade.

**Flexcon BBCAR01 | Flexcon Busmark 5800 | Flexcon Railmark 5300 | MacTac Noodle | MacTac Roodle | 3M IJ40-10 | 3M IJ40-20 Acceptable removable adhesive alternatives are listed for reference only. Boston Barricade does not endorse listed materials and no field testing has been done on our barricade systems by Boston Barricade. Boston Barricade is not liable for any product failure or degradation.

WWW.BOSTONBARRICADE.COM | INFO@BOSTONBARRICADE.COM | NATIONAL SERVICE CENTER 1-866-866-0925

Full Barricade Wrap



- ∴ This option includes covering 100% of the barricade surface with a graphic vinyl wrapping.
- ∴ The vinyl wrapping would include a complete coverage of the front of barricade.
- ∴ Doors and access points would also be considered part of the barricade surface and need to be covered in vinyl fabric treatment.

Note: Barricades that exceed 90 total linear feet (all three sides) are given special exceptions. Graphics will be approved on a per project basis. Graphics and painting should be consistent and cover entire barricade. The percentage of graphics will be taken into consideration as per the length and height of the barricade. All barricade graphics must be approved by the Mall team.

Full Barricade Wrap Examples

