

LOS CERRITOS CENTER

ARCHITECTURAL DESIGN CRITERIA



MACERICH® THE PLACE TO SHOP

ADDENDUM LOG

October 2009

Updated to current layout

February 2014

Revised Walls/Partitions content (a18)

November 2014

Added LED in Lighting (a16)

February 2015

Addition of LED lighting in public Tenant area shall be recessed (a16)

Revised waterproof membrane beneath the finish floor surface
up to 4". (a18)

April 2015

All storefront metal panels must meet LL requirements (this
note must appear on final drawing set.) (a12)

LOS CERRITOS CENTER

**PLEASE VISIT
WWW.MACERICH.COM**

TO VIEW
PLAN SUBMITTAL & APPROVAL
PROCEDURES
and CONTRACTOR RULES &
REGULATIONS

TABLE OF CONTENTS

ARCHITECTURAL DESIGN CRITERIA

General Storefront Requirements	4
Zone Plan	5
Required Seismic Joint Plan & Details.....	6-8
Zone "A"	9-13
Zone "B" (North Side)	14-19
Zone "C" (South Side)	20-23
Zone "D"	24-26
Zone "E"	27-29
Zone "F"	30-32
Storefront Design Criteria	33-36
Awnings and Overhangs	37
Materials	38-39
Interiors	40-42

GENERAL STOREFRONT REQUIREMENTS

LOS CERRITOS CENTER

- All storefront designs and plans are subject to Landlord approval. The overall image should be well coordinated, fully integrating components such as entries, displays and signage.
- Storefronts must be of the highest caliber: expressing state of the art and material quality and meeting or exceeding the very best examples. To achieve this goal, Tenants shall be required to select an Architect who has experience in retail Tenant design.
- Projections or awnings, where required, must be three-dimensional, emphasizing creative, dynamic forms and designs.

The following criteria apply:

1. All storefront construction shall be self supporting from the floor and independent of the building fascia and bulkhead structure. Storefronts may be braced to the overhead structure within the Tenant Space. A minimum of 60 % of the storefront is to be display windows.
2. Three dimensional articulations in both store front plan and height are required for all storefronts in the new tenant areas.
3. Tenants will provide a flush transition between their flooring and the mall flooring.
4. The underside of the entry portal soffit shall be finished to match the storefront. Gypsum board will not be permitted.
5. Stores less than eight hundred (800) square feet shall be required to have durable floors and gypsum board ceilings throughout the sales area.
6. Tenant flooring is required to be specified and installed by Tenant within the entire lease premises including all recessed areas along the storefront.
7. Care must be taken in the proper proportioning of storefronts. Proportions emphasizing the vertical are encouraged. Introduction of clerestories, projection metal canopies and glass breakups to reinforce the pedestrian scale is most desirable.
8. Entry width shall be no greater than 8ft. Closure shall be by swinging type doors recessed at least 3 ft in depth from the face of storefront. Minimum height of entry doors are 9'-0".
9. In addition to meeting all guidelines provided in this manual, Tenants with entrance doors accessed directly from the parking lot are required to meet the design requirements below:
 - Storefront finishes/material must extend to building parapet and beyond to create varied building heights.

- Storefront façade must include pop-out and pop-up design elements to create design interest.
- Three dimensional articulations in both storefront plan and height are required.

Materials used in the construction of storefronts shall be high quality, durable, authentically portrayed and code compliant. The entire storefront area is subject to the Landlord's scrutiny for quality of finishes, detailing and construction methods.

The success of storefront design is largely dependent on how creatively materials and design details are used to develop a unique but well executed image for each Tenant. The following are minimum standards for the use and installation of materials for storefront construction. Proposed materials and colors are to be submitted on a color material sample board to the Landlord for review during the preliminary design review process. (Refer to PLAN SUBMITTAL & REVIEW PROCEDURES for more detailed requirements.)

ZONE PLAN

LOS CERRITOS CENTER




- ZONE "A"
Refer to pages a9-a13
- ZONE "B"
Refer to pages a14-a19
- ZONE "C"
Refer to pages a20-a23
- ZONE "D"
Refer to pages a24-a26
- ZONE "E"
Refer to pages a27-a29
- ZONE "F"
Refer to pages a30-a32


SEISMIC JOINT DETAILS

LOS CERRITOS CENTER

CONTINUED



1 TENANT DEMISING WALL SEISMIC JOINT DETAIL
a7



* NOTE:
T-BAR GRID WIDTH DIMENSION
PER TENANT CEILING TYPE


2 TENANT CEILING SEISMIC JOINT DETAIL
a7

NOTE:
FOR A GYP. BD. CEILING, SEISMIC JOINT DETAIL WOULD BE
SIMILAR TO DETAIL #1 WITH APPROPRIATE SIZED STUDS.


SEISMIC JOINT DETAILS

LOS CERRITOS CENTER

CONTINUED



3 SECTION THRU STOREFRONT SILL @ SEISMIC JOINT
a8 (HEAD DTL. SIMILAR)



4 TENANT STOREFRONT SEISMIC JOINT PLAN DETAIL
a8

NOTE:
FOR SOLID MATERIAL AT STOREFRONT INSTEAD OF GLAZING,
USE DETAIL #1


STOREFRONT REQUIREMENTS

LOS CERRITOS CENTER


ZONE A

Storefront Requirements

- Required storefront height at north side 17'-6"
- Tenant lease line is located 1'-2" from face of Landlord neutral pier.
- 1'-0" max storefront projection above 10'-0" AFF is required in all areas except the no-popout zone. (See No-Popout Zone Plan image below)
- A projecting element is required between 10'-0" to 17'-6" AFF. The design intend is not to have the entire area project out but to create a zone specifying where some sort of projection would be allowed. Consult with Tenant Coordinator regarding this requirement. The design objective is to create movement and interest by popping-out/popping-in. The storefront cannot be on one plane.
- Entry width shall be no greater than 8'-0". Closure shall be by swing type doors recessed at least 3'-0" in depth from face of storefront.
- Expansion tenants will not be required to install accent floor apron. Tenants in this zone will specify and install floor finishes to lease line.



No-Popout Zone Plan




NEUTRAL PIER DETAIL

LOS CERRITOS CENTER

CONTINUED

NEUTRAL PIER CONDITION @ ZONE A

NEUTRAL PIER DTL. @ TENANT STOREFRONTS



 - Area by Tenant : Constructed by Tenant Contractor


NEUTRAL PIER DETAIL

LOS CERRITOS CENTER

CONTINUED

ZONE "A"
SECTION DETAIL

SECTION DTL. @ ZONE "A" TENANTS




NEUTRAL PIER DETAIL

LOS CERRITOS CENTER

CONTINUED

ZONE "A" SECTION DETAIL

SECTION DTL. @ ZONE "A" TENANTS



BULKHEAD STUDY

LOS CERRITOS CENTER

ZONE "A"
BULKHEAD STUDY - NORTH-FACING RENDER



Image rendered by Kitchen Sink Studios


STOREFRONT REQUIREMENTS

LOS CERRITOS CENTER

ZONE "B" NORTH SIDE

Storefront Requirements

- First Tenant in existing portion of Zone "B" to extend any neutral pier adjacent to their space out into the common area per details provided.
- Required storefront height at north side 17'-6"
- Tenant lease line is located 1'-2" from face of Landlord neutral pier.
- 2'-0" max storefront projection above 10'-0" AFF is required. A projecting element is required between 10'-0" to 17'-6" AFF. The design intend is not to have the entire area project out but to create a zone specifying where some sort of projection would be allowed. Consult with Tenant Coordinator regarding this requirement. The design objective is to create movement and interest by popping-out/popping-in. The storefront cannot be on one plane.
- Entry width shall be no greater than 8'-0". Closure shall be by swing type doors recessed at least 3'-0" in depth from face of storefront.
- Tenant to install Tenant's durable floor covering to lease line. Tenant is responsible to bring Tenant's Floor covering to mall's common area tile at lease line, and make any adjustments in grade change to meet ADA requirements. Tenant to install Tenant's floor covering in Tenant entry door vestibule.




NEUTRAL PIER DETAIL

LOS CERRITOS CENTER

CONTINUED

NEUTRAL PIER CONDITION @ ZONE B

NEUTRAL PIER DTL. @ TENANT STOREFRONTS



 - Area by Tenant : Constructed by Tenant Contractor


NEUTRAL PIER DETAIL

LOS CERRITOS CENTER

CONTINUED

ZONE "B"
NORTH SIDE SECTION DETAIL

SECTION DTL. @ NORTH-FACING TENANT



NEUTRAL PIER DETAIL

LOS CERRITOS CENTER

CONTINUED

ZONE "B"
NORTH SIDE - BULKHEAD STUDY



ELEVATION CONTINUES TO PAGE a10

BULKHEAD STUDY

LOS CERRITOS CENTER

ZONE "B"
NORTH SIDE - BULKHEAD STUDY (cont'd)



ELEVATION CONTINUED FROM PAGE a9

BULKHEAD STUDY

LOS CERRITOS CENTER

ZONE "B"
NORTH SIDE - BULKHEAD STUDY (cont'd)



STOREFRONT REQUIREMENTS


LOS CERRITOS CENTER

ZONE "C" SOUTH SIDE

Storefront Requirements

- Required storefront height at south side 14'-0"
- Tenant leaseline is located 1'-2" from the face of Landlord neutral pier. Tenant finishes must extend to this line.
- The face of the storefront needs to be aligned with the LL bulkhead above.
- Entry width shall be no greater than 8 ft. Closure shall be by swing type doors recessed at least 3 ft. in depth from face of storefront.
- Tenant to install Tenant's durable floor covering to lease line. Tenant is responsible to bring Tenant's Floor covering to mall's common area tile at lease line, and make any adjustments in grade change to meet ADA requirements. Tenant to install Tenant's floor covering in Tenant entry door vestibule.

EXISTING




NEUTRAL PIER DETAIL

LOS CERRITOS CENTER

CONTINUED

NEUTRAL PIER CONDITION @ ZONE C

NEUTRAL PIER DTL. @ TENANT STOREFRONTS



 - Area by Tenant : Constructed by Tenant Contractor



NEUTRAL PIER DETAIL

LOS CERRITOS CENTER

CONTINUED

ZONE "C"
SOUTH SIDE - SECTION DETAIL

SECTION DTL. @ SOUTH-FACING TENANT



TENANT STUDY

LOS CERRITOS CENTER

ZONE "C" TENANT STUDY




STOREFRONT REQUIREMENTS

LOS CERRITOS CENTER

ZONE "D"

Storefront Requirements

- Required storefront height 14'-0"
- Tenant leaseline is located 20"- 22" from face of Landlord neutral pier.
- 1'-0" storefront projection above 9'-0" AFF is required. A projecting element is required between 9'-0" to 14'-0" AFF. The design intend is not to have the entire area project out but to create a zone specifying where some sort of projection would be allowed. Consult with Tenant Coordinator regarding this requirement. The design objective is to create movement and interest by popping-out/popping-in. The storefront cannot be on one plane.
- Storefronts must pop-out and pop-up into the mall.
- Storefronts located under shallow vaulted ceilings with an extended mall fascia (16'~3" AFF) are in special pop-up zones and are required to extend selected elements of the storefront above the 12' Landlord fascia line. Such elements may project from or apply to the Landlord fascia up to 14ft. above the mall floor. Verify exact height with Tenant Coordinator.
- Tenants may project selected elements of the storefront (located 9 ft. or more a.f.t.) up to 3ft. into the mall, measured from face of mall fascia. Overhead projections shall be a layering of architectural elements and never be overly massive in nature.
- Verify exact exterior flooring apron configuration required with Tenant Coordinator prior to construction start.
- Tenant to install Tenant's durable floor covering to lease line. Tenant is responsible to bring Tenant's Floor covering to mall's common area tile at lease line, and make any adjustments in grade change to meet ADA requirements. Tenant to install Tenant's floor covering in Tenant entry door vestibule.



EXISTING




NEUTRAL PIER DETAIL

LOS CERRITOS CENTER

CONTINUED

NEUTRAL PIER CONDITION @ ZONE D

NEUTRAL PIER DTL. @ TENANT STOREFRONTS



 - Area by Tenant : Constructed by Tenant Contractor


NEUTRAL PIER DETAIL

LOS CERRITOS CENTER

CONTINUED

ZONE "D"
SECTION PIER DETAIL

SECTION DTL. @ ZONE "D"




STOREFRONT REQUIREMENTS

LOS CERRITOS CENTER

ZONE "E"

Storefront Requirements

- Required storefront height 17'-0". In areas with dropped soffit contact the mall Tenant Coordinator for height requirement.
- Tenant leaseline is located 2'-2" from face of Landlord neutral pier.
- 1'-0" storefront projection above 10'-0" AFF is required from leaseline. A projecting element is required between 10'-0" to 17'-0" AFF. The design objective is to create movement and interest by popping-out/popping-up. Storefront cannot be on one plane. Max 3' projection will be allowed from Landlord bulkhead.
- Storefronts must both pop out and pop up into the mall.
- Storefronts located under high mall ceilings (20'-0" AFF) are in special pop up zones and are required to incorporate special design features which extend selected elements of the storefront above the 12' Landlord fascia. Such elements may project from, apply to, penetrate into, or penetrate through the Landlord fascia up to 17' above the mall floor.
- Tenant to install Tenant's durable floor covering to lease line. Tenant is responsible to bring Tenant's Floor covering to mall's common area tile at lease line, and make any adjustments in grade change to meet ADA requirements. Tenant to install Tenant's floor covering in Tenant entry door vestibule.



EXISTING




NEUTRAL PIER DETAIL

LOS CERRITOS CENTER

CONTINUED

NEUTRAL PIER CONDITION @ ZONE E

NEUTRAL PIER DTL. @ TENANT STOREFRONTS



 - Area by Tenant : Constructed by Tenant Contractor


NEUTRAL PIER DETAIL

LOS CERRITOS CENTER

CONTINUED

ZONE "E"
SECTION DETAIL

SECTION DTL. @ ZONE "E"



STOREFRONT REQUIREMENTS

LOS CERRITOS CENTER


ZONE "F"

Storefront Requirements

- Required storefront height is 12'-0"
- Tenant leaseline is with the face of Landlord neutral pier.
- The face of the storefront needs to be aligned with the LL bulkhead above.
- Tenant to install Tenant's durable floor covering to lease line. Tenant is responsible to bring Tenant's Floor covering to mall's common area tile at lease line, and make any adjustments in grade change to meet ADA requirements. Tenant to install Tenant's floor covering in Tenant entry door vestibule.



EXISTING




NEUTRAL PIER DETAIL

LOS CERRITOS CENTER

CONTINUED

ZONE "F"
SECTION DETAIL

SECTION DTL. @ ZONE "F"



STOREFRONT DESIGN CRITERIA

LOS CERRITOS CENTER

GENERAL MATERIAL REQUIREMENTS

Storefront design cannot consist of glazing only. Tenant must introduce other design elements/materials as per Landlord's requirements.

Window configuration and glazing comprise the largest compositional elements of storefronts. They establish a great deal of the design character and define the relationship between interior and exterior. The glazing systems establish the framework for the display of the Tenants' image and merchandise. Size, proportion, and pattern should be carefully considered.

The transparent surfaces of the storefront serve an important design role to the storefront and the interior by creating an architectural display area. The use of glazing should be creatively explored and carefully detailed. The following criteria applies:

1. Large panes of glazing must be of sufficient thickness to meet code and be properly supported.
2. All glass shall be tempered.
3. In frameless assemblies, glass panel joint details must be top quality and are subject to strict Landlord review. Glazing edges must be polished, ground or chamfered. Glazing channels at corner conditions must be mitered.
4. Tenants may be required to provide seismic clips to stabilize tall expanses of glass. Silicone sealant at glazing joints is not permitted.
5. Reflective glass (including the extensive use of mirror) and/or tinted glass is not permitted on storefronts or in the storefront entry zone.
6. Tenants are not restricted to asymmetrical design, particular proportions, sizes, or types of glazing systems.
7. Tenants are encouraged to "open-up" their store front by extending their glazing to the extents of their leaseline.
8. Butt-joint glazing is encouraged for show windows that infill larger storefront forms. Glass shall be clear polished plate or tempered glass as required by code.
9. Window mullions are required to meet all material and finish standards.
10. Glazing should be predominantly clear to emphasize merchandise display.
11. Decorative glazing such as colored, beveled, sandblasted or etched glass may be used to create accent pattern and interest.
12. Glazing shall be a minimum of ½" thick, clear tempered glass where used in conjunction with mullions or framed systems.



STOREFRONT DESIGN CRITERIA

LOS CERRITOS CENTER

CONTINUED

ROLLING GRILLE DESIGN GUIDELINES

Landlord strongly encourages the use of glass doors. In the event a rolling grille is required by the Tenant, Landlord will only consider this option if Tenant meets all of the guidelines identified in this document. All storefront designs are subject to Landlord approval.

Guideline 1

Tenants with a rolling grille are required to follow the guidelines listed below:

- Entry grille opening not to exceed 30% of the width of the storefront
- Maximum 40-50% of storefront must be display windows
- Minimum 15-30% of storefront must be hard surface material



Guideline 2

Tenant storefronts cannot be on one plane; three-dimensional storefront articulations are required. Tenant storefronts must be visually interesting.



STOREFRONT DESIGN CRITERIA

LOS CERRITOS CENTER

CONTINUED

Guideline 3

Tenant storefronts must include a portal entrance. The objective is to clearly define the entrance while enhancing the overall design of the storefront.



Guideline 4

Maximum opening height allowed for rolling grille is 10'-0".



STOREFRONT DESIGN CRITERIA

LOS CERRITOS CENTER

CONTINUED

Guideline 5

Rolling grille system must be concealed from view; tracks shall not be visible in walls, floors or ceiling. Horizontal rolling grilles are not allowed. Key switches, buzzer, etc., shall be hidden from view.

Guideline 6

A finished ceiling design is required at the entrance.



Guideline 7

Pedestal type security systems are not allowed. Tenant can specify concealed system. Tenant to submit specifications to Landlord for approval.



STOREFRONT DESIGN CRITERIA

LOS CERRITOS CENTER

CONTINUED

AWNING DESIGN GUIDELINES

AWNING TYPE

Creative materials and forms of awnings are encouraged to promote identity among Tenants.

- Creative, imaginative, unusual shapes
- Semi spherical
- Multiple
- Unusual materials such as louvers, wood, wire, metal, etc. subject to review by Landlord's Tenant Coordinator.

AWNING SIGNAGE

Signage may be incorporated into the awning design which may be painted, silk screened, or integrated within the awning itself. The signage should be proportional to the awning size so that it does not clash or overpower the structure.

Wording shall include Tenant's name and/or logo only. Taglines will not be permitted.

AWNING LOGOS

Logos are highly encouraged on awnings. Symbols applied to awnings provide a highly effective method of Tenant identity while adding color and interest to the storefront design. Logos should be silk-screened or painted when on a fabric awning. Three dimensional 'medallion type' logos should be integrated when the awning is designed out of glass and/or metal. Size of logo should be proportional to the overall size of the awning, subject to Landlord approval. Logo shall be submitted along with awning and signage shop drawings.

- The lowest point of any awning or shade element shall be 8'-0" above the finished floor. It is the designer's responsibility to ensure that awnings conform to all applicable codes.
- Awning framework should be painted to match the awning fabric.
- Materials such as plastic or vinyl will not be permitted.
- In no case shall awnings be enclosed on the underside and internally illuminated, allowing the awning to function as a canned light source.
- Awnings must be cleaned and maintained in good condition by Tenant at Tenant's expense.

PATIO ENCLOSURES

Patio enclosures are to be created from solid structures. Fence type of enclosure are not allowed.

PATIO FURNITURE

All patio furniture may be subject to City review and approval.



STOREFRONT DESIGN CRITERIA

LOS CERRITOS CENTER

CONTINUED


OVERHANGS

Overhangs are permitted in storefronts provided that they are an integral part of the storefront design. The underside of overhangs must be articulated with architectural elements such as brackets, coffers or exposed beam-ends.



UMBRELLAS

Umbrellas are only allowed in the Tenant's exterior Leased Premises and cannot overhang into the public right-of-way. Umbrellas should be small in scale (maximum 6'-0" in diameter) and no more than 9'-0" high at the peak. Wood or wrought iron are the only acceptable materials for the umbrella structure. No insignia, graphics or text is permitted on the umbrella fabric. The umbrella fabric must be flame retardant material in a color approved by Landlord's Tenant Coordinator.



MATERIALS

LOS CERRITOS CENTER

GENERAL MATERIAL REQUIREMENTS

- The use of natural materials is encouraged. All materials used in storefronts must be durable and non-corrosive.
- Careful attention to the detailing or joinery of differing materials is necessary. A carefully defined edge must be established between different materials and surfaces on the storefront as well as between the Tenant and Landlord finishes.
- All finished store materials within 6'-0" of the storefront point of closure shall be durable such as glass, tile, metal, stone, terrazzo, plaster, hardwood or similar materials approved by the Landlord. Reflective wallpaper, vinyl wall coverings, plastic laminates, mirror, slatwall or tambour will not be permitted.
- Any wood material used for storefront construction must comply with all code requirements.

Metals

- All storefront metal panels must meet LL requirements below (this note must appear on final drawing set):
- All seams between metal panels must be identified on the storefront elevation and must be properly addressed during design review process. Metal panels will not be allowed to directly come into contact with

adjacent panel. Reveals, turn-in seams, welding or similar must be specified and detailed out on the plans for approval.

- Minimum 18 gauge metal panels are required. This must be called out on their plans for approval
- No visible fasteners.
- Min ½" thick fire-rated plywood substrate is required and must be called out on the plans.
- High quality is expected for all metal applications. Metal such as shop-painted aluminum and steel, stainless steel, solid brass, bronze, pewter, or enamel coated steel may be used for hardware, trim and panels when well designed and detailed.



- Lap joints and seams must be even and straight and concealed when possible. Outside corners are to be mitered or continuous break shaped.
- Fabrication must be either heavy gauge material or thinner gauge material shop laminated to solid backing. In no case is oil canning (resulting from light reflection from an uneven or buckled surface), scratches, warps, dents, occlusions, visible seams or other imperfections allowed.
- Sealants on natural metals are required to prevent tarnishing and must be maintained by Tenant at Tenant's expense.
- Textured or brushed stainless steel, galvanized, sandblasted and etched metals are encouraged in creative applications.
- Unique treatments such as patina, rusted, etched and imprinted metals will be considered for special design objectives.
- Polished metals should be solid, not plated and limited to accent trim.
- Stimulated finishes, such as metallic laminates and anodized aluminum are not permitted.

MATERIALS

LOS CERRITOS CENTER

CONTINUED

Stone

Granite, marble, limestone, slate, adoquin and other natural stone materials may be used in storefront applications. Stone may be polished, unpolished, sandblasted, flamed, honed, split-face or carved. Careful craftsman-like attention to detail is required at all connections and transitions to other materials.

- Edge details must prevent visible unfinished edges. Exposed edges must be quirk mitered, chamfered or polished to match adjacent surface finish.
- The transition between stone and adjoining materials must be defined by use of metal reveals.
- Stone used as a paving material must be flush when meeting other flooring materials.
- Natural stone must be protected against staining and discoloration by means of sealers appropriate to the material.

Wood

Painted or stained wood may be used in many design applications, such as window frames, decorative trim or molding and for solid areas, such as decorative bulkheads. In some cases, it may be used for larger architectural elements, such as columns and entablatures. Wood paneling and plank construction are not acceptable unless presented in a highly imaginative concept and approved by the Landlord.

- All detailing and construction is to be executed in a high quality, craftsman-like manner.
- Wood used in the construction of the storefront must be kiln dried, mill quality hardwood and must meet local flame spread requirements (Class III 76-200).
- Painted wood must have a shop quality enamel finish.
- Wood without a paint finish must receive a clear, preservative sealant.
- Extensive use of natural wood finishes is discouraged. All stains and finishes must be approved by Landlord's Tenant Coordinator.

Tile

Tile may be used in diverse applications. Its use is encouraged to introduce light, decorative texture or graphic quality to a storefront.

- Porcelain, ceramic or glass tiles in glazed or natural finishes may be used as accents and in limited field applications. Patterns used over large areas are expected to have a sophisticated, well executed design concept.
- Small and intricate mosaic tile patterns may be utilized for detail and accent only.

- All tile must be carefully detailed at outside corners with bull nose edges or special corner trims. Lapped or butt joints are not permitted.
- Grout color should match the background color of the tile so as not to emphasize a grid pattern.



MATERIALS

Pre-cast Stone and Concrete

Many pre-cast stone and concrete products are currently available that may be acceptable for storefront applications. The use of these materials is at the discretion of the Landlord.

Plaster

Plaster, cement plaster (stucco) and Venetian plaster finishes may be considered for limited storefront applications, provided the finish texture is a light dash, sand or smooth finish. Plaster or stucco finishes should be used in combination with other high quality materials such as stone or metal and not be the primary storefront material.

Faux Finishes

Faux finishes may be used at the Landlord's discretion.

- Actual samples of the faux finish must be submitted to the Landlord. Photographs of previous examples are helpful but may not be substituted for an actual sample.
- Faux finishes must be executed by a commercial artisan specializing in that medium.

Painted Surfaces

Any paint applied to the materials in the storefront is to be specified and is under the approval of the Landlord's Design Consultant. All paint should be of high quality for an even and durable finish. The following criteria must also be observed:

- Painted wood surfaces must be properly prepared and sealed prior to the application of a high grade enamel.
- Painted metal shall have a factory applied finish of baked enamel or powder coat treatment.
- Painted gypsum wall board will be allowed only within the interior of the storefront, not on the exterior storefront.
- Required MDF finish process:
 - 1 Coat primer, 2 coats finish (sprayed and sand between each step).
 - * Specify drywall behind the MDF
 - Min. thickness for MDF is ¾" on storefronts.

Prohibited Materials

The following is a list of prohibited materials. In rare instances, special consideration may be given for the use of a prohibited material if its application is highly original, creative and essential to the theme or design concept of the storefront. Exceptions will be determined by the Landlord during design review:

- Plastic laminates.
- Glossy or large expanses of acrylic or Plexiglas
- Pegboard
- Mirror
- Highly polished or plated metals - except as trim
- Reflective glass
- Simulated materials such as brick, stone or wood veneer
- Distressed woods such as pecky cedar, rough sawn lumber, softwoods
- Anodized aluminum
- Vinyl, fabric or paper wall coverings
- Plywood or particle board
- Sheet or modular vinyl
- Luminous ceilings, including “egg crate”
- Vinyl awnings
- Shingles, shakes, rustic siding
- 4”x4”, 6”x6”, 12”x12” tiles
- Glazed tiles
- Other materials deemed unacceptable by the Landlord. 4”x4”, 6”x6”, 12”x12” tiles
- Glazed tiles
- Other materials deemed unacceptable by the Landlord.

INTERIORS

LOS CERRITOS CENTER

Tenants are required to produce high quality, well detailed and executed interior solutions that are unique, imaginative and stylized.

The store interior is typically viewed as a continuation of the storefront in design and materials. Walls are to have modulation of display systems and built in architectural components that reinforce the store design theme.

Tenants with above normal sound levels must provide sound isolation in demising walls and in ceilings within 4'-0" of demising partitions. Security devices are to be entirely concealed within the store design elements. Under floor or in ceiling systems are preferred. Non-combustible and or fire-resistant materials are required within the entire lease area. Interior design must meet accessibility guidelines enforced by national or local jurisdictions, including the Americans with Disabilities Act. All materials acceptable or prohibited at the storefront are applicable to the store interior.

Design Control Area (DCA)

The DCA is the area at the front of the Tenant space that extends from the point of closure to all points 6'-0" into the space. The DCA includes all display windows and retail graphics, display fixtures, signs, materials, finishes, color and lighting fixtures within the area.

The DCA can be considered an extension of the storefront presentation and should convey a store's merchandise identity and generate activity. It should convey excitement and give the consumer a reason to stop at the store. Proportion and scale of objects within the DCA is a specific concern in successful

design. As with the actual storefront design, the objects within it must be in proportion to the space around them. Incorporating elements that raise from the floor or lower from the ceiling can control the scale of the DCA. Pedestals to display merchandise or light pendants hanging down can be examples of object forms that can control scale. These solutions can vary and are somewhat different from traditional and typical display zones.

Tenants shall use the following design criteria for displays within the DCA:

- Design drawings shall have a display layout plan. The layout plan shall have cut sheets for fixture and/or mannequin types and include photographs of any existing storefronts a Tenant may have that will enhance the layout plan. A rendering is required if photographs are not available.
- Displays shall be deliberate and designated as integrated elements of the storefront.
- Security devices must be concealed; freestanding pedestals are not permitted.
- Large temporary signs for special sales or clearances shall not be hung in the DCA including any signs taped or suction cupped to storefront glazing.
- No pegboard, slatwall or metal shelving of any kind may be placed in or extend into any part of the DCA.

INTERIORS

LOS CERRITOS CENTER

CONTINUED

Ceilings

Ceilings Tenants can choose to have an open ceiling which may incorporate an open grid or be painted. Tenant installed ceilings shall conform to the following criteria:

- Tenant sales floor ceiling is to be a minimum of 12'-0" aff. Actual conditions to be field verified.
- Hard surface ceiling required through the entire storefront DCA. This distance shall be a minimum width of six feet (6'-0") in from the innermost point of closure line.
- Custom ceiling treatments are required. Multi level gypsum wallboard, concealed spline, decorative patterned ceiling panels and other "high-tech" materials are encouraged. The use of ceilings on a single plane is not permitted. The use of beams, steps and 'islands' are required along with the imaginative use of lighting fixtures and fittings.
- Fire sprinkler heads are to be fully recessed in hard or acoustical ceilings.
- Standard 24" x 48" acoustical panels are not allowed in the sales area.
- Ceiling concepts implementing exposed structure, electrical and mechanical systems must be coordinated with the Landlord for specific technical and design requirements.

- All suspended ceilings shall stop within 2'-0" of the partitions within the Tenant sales area. Suspended ceilings shall be terminated with a soffit, cove lighting detail, or other means of a finished edge along partition walls. Exposed edges shall be properly finished. Wall to wall suspended ceilings are not allowed.
- All ceilings, related framing, blocking and accessories shall be noncombustible. No combustible materials may be used above finished ceiling surfaces.

Lighting

Lighting can greatly contribute to the design of a Tenant's store, emphasizing architectural forms, highlighting signage, and adding color and visual drama to walls and other design elements. The creative use of dramatic lighting is encouraged at entries, show windows and merchandise displays.

- The DCA of the Tenant space must employ lighting fixtures consistent with the character of the storefront design. All lighting fixtures within DCA must be recessed downlights, MR16 low voltage, or similar types. Fluorescent fixtures will not be permitted.

- Track lights shall be finished to match ceiling; other finishes to be approved by Landlord. Track heads are to be accommodated with shields or louvers. Track lights are not allowed in DCA.
- Fixtures must be positioned so that bright glare is not directed onto the public areas.
- All fluorescent, incandescent, LED and HID lighting fixtures in public Tenant areas, other than track and decorative fixtures, shall be recessed with no directly visible lamp sources.
- Bare lamp fluorescent or incandescent fixtures may be used only in concealed areas and/or stockrooms. Fluorescent fixtures shall have a maximum size of 2' x 2' and have silver parabolic louvers or metallic finished eggcrate diffusers. All lighting fixtures shall bear the U.L. label.
- Concealed light coves to highlight architectural elements within the storefront are highly encouraged
- Wall sconces may be used to cast light onto storefront forms, provided that bare bulbs are not exposed and that the finish and form of these fixtures coordinate with the overall storefront design. Fixture cut sheets will be required to be submitted if this light form is used.

INTERIORS

LOS CERRITOS CENTER

CONTINUED

Lighting (cont'd)

- Exterior mounted decorative light fixtures are encouraged where appropriate for the storefront design concept. Fixture cut sheets must be submitted for review.
- All lighting must be reviewed and approved by Landlord. Tenant is responsible for maintenance of all lighting within the entire Leased Premises.
- Tenant shall comply with all applicable energy conservation and building codes unless it adheres to the kinetic or flashing lighting requirements.
- All showcases and display cases must be adequately lit and ventilated. Direct visual exposure of incandescent bulbs and/or fluorescent tubes is prohibited.

Walls/Partitions

- Demising walls may be provided between two Tenants and/or Tenant and exit/service corridors. Walls will typically consist of 3 $\frac{3}{8}$ " or 6" metal studs (provided by Landlord), and $\frac{5}{8}$ " type X fire rated drywall, taped from floor to bottom of roof deck, or deck above (or as required by governing code) on each side (provided by Tenants). At Landlord's option, demising partitions shall be of unfinished masonry, concrete or metal studs. Demising walls are not designed to accommodate

cantilevered or eccentric loads. If Tenant plans to use a demising wall for support of shelf standards, light soffits or heavy attachments, Tenant shall reinforce the wall as required by providing additional steel studs or independent supports for the shelf standards.

- Existing corridor separation walls adjacent to Tenant's space have finishes by the Landlord on the corridor side only. Tenant shall finish the interior as required by code for fire rated wall.
- Demising walls and ceiling shall be sound insulated to achieve a minimum STC rating of 50 by Tenants who produce above 80 dB (including but not limited to music stores, arcades, etc.) The Landlord will strictly enforce all Tenant's right to quiet enjoyment of their Leased Premises.
- Tenant shall protect fire proofed columns and braces with gypsum board, and furr as required.
- The following are required for hair salons, pet shops and all food preparation type Tenants:
 - a. Walls containing "wet" areas to be constructed of metal studs with water resistant $\frac{5}{8}$ " type "x" gypsum board.
 - b. Demising walls of pet shops shall have sheet metal installed on studs, behind drywall, up 3'-0" from floor.

- Tenant Premises adjacent to a two-hour wall condition will be required to apply two (2) layers of $\frac{5}{8}$ " type "x" gypsum board or other material to adequately complete the wall construction to provide a two-hour rating.
- Stockroom Partitions. When Tenant chooses not to install a ceiling within Tenant's stockroom, Tenant shall extend the partition separating the stockroom from other areas of the store, to the underside of the structure above in order to isolate the stockroom from the sales area attic space. Tenant to verify if this is allowed by code.
- Wall Finishes. All interior wall surfaces must be finished in an appropriate manner and be in compliance with all applicable codes. All Tenant space interior wall finishes are to meet a Class III flame spread rating or as required by local code.
- Metal or plastic laminate inserts are required for slatwall. No visible substrate at slats. Slatwall is not allowed within the first 8'-0" of store entry doors.
- Recessed wall standards are permitted. No open shelving with visible brackets or surface mounted systems are allowed.

INTERIORS

LOS CERRITOS CENTER

CONTINUED

Floor and Wall Base

Tenants shall install a floor covering in Tenant's sales area which conform to the following criteria:

- Hard surface floor and base required through the entire DCA, including any permitted pop out areas. Carpet, vinyl or rubber materials of any sort will not be permitted within the DCA.
 - Exposed concrete floors shall be sealed.
 - Wood installations shall be hardwood with wear resistant surface.
 - Ceramic, quarry and stone tile installations must be commercial grade with non-slip surface.
 - Carpet must be commercial grade and must have proper fire ratings to meet local codes. Carpeting will not be permitted where color, quality or weave is not suitable for high traffic areas. Note: Carpet may not be used at the store entry within the DCA.
 - Sheet or modular vinyl may be used in support or stock rooms not visible from the sales area.
 - Tenant shall provide a transition strip between opposing floor finishes. This includes but is not limited to carpet and wood, or carpet and tile.
- Tenant shall provide wood base in sales area.
 - All seams must be tight and any seepage of adhesive is unacceptable.
 - All vinyl to existing flooring must be a smooth transition. No tape or aluminum thresholds allowed.
 - Any floor materials other than those mentioned above will not be allowed. Samples of all finishes must be submitted for approval and included in Tenant's preliminary submissions.

Toilet Room Requirements

- Toilet facilities shall be designed in compliance with all applicable ADA & Building Department Codes.
- Provide a 3" floor drain and cleanout.
- Each restroom must have an exhaust system.
- Floor finishes in toilet rooms shall be ceramic tile with a coved 6" base. Tenant is required to provide a waterproof membrane beneath the finish floor surface up to a height of 4'-0" along all walls.
- Toilet room walls and ceiling shall be constructed of metal studs with water-resistant 5/8" type "x" gypsum board applied to the interior side of the toilet room. At

a minimum, interior wall finishes shall be a light colored enamel paint with a 4' high wainscot extending 24" on each side of, and 24" beyond the front portion of any water closet or urinal.

- The ceiling shall be a minimum of 8'-0" above the finished floor level, be constructed of 5/8" type "x" water resistant gypsum and be finished with enamel paint. The ceiling shall contain a vent, which shall be connected to the Landlord's exhaust system, or as pursuant to the Center requirements.

INTERIORS

LOS CERRITOS CENTER

CONTINUED

Clearance Requirements:

(Refer to City document “City Required Clearances (Kiosk Storefronts).pdf” on website for more information.)

- 15’ Needs to be maintained between kiosks and inline storefronts and then 20’ between any two kiosks

Exiting

All retail Tenant spaces must provide two exits from the premises if required by code and/or Landlord’s Tenant Coordinator. All exits must be engineered in compliance with all applicable ADA & Building Department Codes.

Door Information

- A. Doors are required and are to be minimum of 8’-0” in height.
- B. Single leaf, pair or multiple leaf doors shall not be less than 3’-0” wide per leaf and shall be hinged, decorative folding, or pivot type doors.
- C. All secondary exit doors shall be backset so that the door does not swing into the corridor, or exit passageway. Exit doors shall comply with

this criteria and with local building codes. Every required exit shall be marked by a readily visible illuminated exit sign.

- D. Rear Service / Exit Doors: Landlord may provide a rear service / exit door if required by code, and space has a demising wall common to a mall service corridor. The service / exit door, if provided, shall be of hollow metal construction and provided with a lockset and standard door closer. If Landlord provides no service / exit door, Tenant at Tenant’s sole cost and expense, shall provide a service / exit door as required by code. Any service / exit door(s) installed by the Tenant shall be located subject to the approval of the Landlord. At the Tenant’s sole cost and expense, Tenant may relocate the service / exit door subject to the prior approval of the Landlord’s Tenant Coordinator. The performance of any such relocation shall include the repair and replacement of any Landlord’s work, and is subject to acceptance by the landlord.